


N-Channel Enhancement Mode MOSFET

Features

- Low $R_{ds(on)}$ for low conduction loss
- Reliable and Rugged
- ROHS Compliant & Halogen-Free

Pin Description



Applications

- Power Management in Desktop Computer
- DC/DC Converters

V_{bss}	80	V
$R_{DS(ON)-Max}$	6.2	m Ω
I_D	93	A

Absolute Maximum Ratings ($T_J=25^\circ\text{C}$, Unless Otherwise Noted)

Symbol	Parameter	N-Channel	Unit
V_{bss}	Drain-Source Voltage	80	V
V_{gss}	Gate-Source Voltage	± 20	V
T_J	Maximum Junction Temperature	150	$^\circ\text{C}$
T_{STG}	Storage Temperature Range	-55 to 150	$^\circ\text{C}$
$I_{DM}^{①}$	Pulse Drain Current Tested	$T_c=25^\circ\text{C}$	372 A
I_D	Continuous Drain Current	$T_c=25^\circ\text{C}$	93 A
		$T_c=100^\circ\text{C}$	58
P_D	Maximum Power Dissipation	$T_c=25^\circ\text{C}$	125 W
		$T_c=100^\circ\text{C}$	50
$E_{AS}^{②}$	Avalanche Energy, Single pulse	625	mJ

Thermal Characteristics

Symbol	Parameter	Rating	Unit
$R_{\theta JA}^{③}$	Thermal Resistance-Junction to Ambient	62.5	$^\circ\text{C}/\text{W}$
$R_{\theta JC}$	Thermal Resistance-Junction to Case	1	$^\circ\text{C}/\text{W}$

Note ① : Max. current is limited by bonding wire.

Note ② : UIS tested and pulse width are limited by maximum junction temperature 150°C .

Note ③ : Surface Mounted on 1in^2 FR-4 board with 1oz.

**N-Channel Enhancement Mode MOSFET****Electrical Characteristics** ($T_J=25^{\circ}\text{C}$, Unless Otherwise Noted)







Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Static Electrical Characteristics						
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS}=0V, I_D=250\mu A$	80	---	---	V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS}=75V, V_{GS}=0V$	---	---	1	μA
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu A$	2	---	4	V
I_{GSS}	Gate Leakage Current	$V_{GS}=\pm 20V, V_{DS}=0V$	---	---	± 100	nA
$R_{DS(ON)}$	Drain-Source On-state Resistance	$V_{GS}=10V, I_D=40A$	---	5.4	6.2	m Ω
Dynamic Characteristics ^⑤						
C_{iss}	Input Capacitance	$V_{GS}=0V,$ $V_{DS}=30V,$ Freq.=1MHz	---	4900	---	pF
C_{oss}	Output Capacitance		---	440	---	
C_{rss}	Reverse Transfer Capacitance		---	145	---	
$T_{d(on)}$	Turn-on Delay Time	$V_{GS}=10V, V_{DD}=30V,$ $I_D=1A, R_{GEN}=6\Omega$	---	23	---	nS
T_r	Turn-on Rise Time		---	51	---	
$T_{d(off)}$	Turn-off Delay Time		---	66	---	
T_f	Turn-off Fall Time		---	23	---	
Q_g	Total Gate Charge	$V_{GS}=10V, V_{DS}=60V,$ $I_D=40A$	---	115	---	nC
Q_{gs}	Gate-Source Charge		---	20	---	
Q_{gd}	Gate-Drain Charge		---	50	---	
Source-Drain Characteristics						
V_{SD} ^④	Diode Forward Voltage	$I_S=40A, V_{GS}=0V$	---	0.87	1.2	V
T_{rr}	Reverse Recovery Time	$I_S=40A, V_{GS}=0$ $di_F/dt=100A/\mu s$	---	41	---	nS
Q_{rr}	Reverse Recovery Charge		---	86	---	nC






Note ④ : Pulse test (pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$).


Note ⑤ : Guaranteed by design, not subject to production testing.

N-Channel Enhancement Mode MOSFET

Typical Characteristics



N-Channel Enhancement Mode MOSFET


N-Channel Enhancement Mode MOSFET
DFN5×6 Package Outline Data

DIMENSIONS (unit : mm)

Symbol	Min	Typ	Max	Symbol	Min	Typ	Max
A	0.90	1.02	1.10	D	4.90	4.98	5.10
D ₁	4.80	4.89	5.10	E	5.90	6.11	6.25
E ₁	5.65	5.74	5.95	e	3.72	3.80	3.92
e ₁	--	0.5	--	e ₂	--	1.	--
f	--	3.8	--	f ₁	0.31	0.37	0.51
f ₂	--	0.6	--	H	--	3.	--
H ₁	0.59	0.63	0.79	H ₂	0.26	0.28	0.32
L	3.35	3.45	3.65	L ₁	--	1.	--
v	--	0.1	--	w	0.64	0.68	0.84
y	--	0.3	--				