


N-Channel Enhancement Mode MOSFET
Features

- Fast switching speed
- Reliable and Rugged
- ROHS Compliant & Halogen-Free

Pin Description

Applications

- Power Management in Desktop Computer
- DC/DC Converters

V_{DSS}	200	V
$R_{DS(ON)-Typ}$	9.5	m Ω
I_D	110	A

Absolute Maximum Ratings ($T_J=25^{\circ}C$, Unless Otherwise Noted)

Symbol	Parameter	N-Channel	Unit
V_{DSS}	Drain-Source Voltage	200	V
V_{GSS}	Gate-Source Voltage	± 20	V
T_J	Maximum Junction Temperature	-55 to 150	$^{\circ}C$
T_{STG}	Storage Temperature Range	-55 to 150	$^{\circ}C$
E_{AS}	Single Pulse Avalanche Energy	2000	mJ
$I_{DM}^{①}$	Pulse Drain Current Tested	440	A
I_D	Continuous Drain Current	$T_C=25^{\circ}C$	A
	Continuous Drain Current	$T_C=100^{\circ}C$	A
P_D	Maximum Power Dissipation	$T_C=25^{\circ}C$	W

Thermal Characteristics

Symbol	Parameter	Rating	Unit
$R_{\theta JA}^{③}$	Thermal Resistance-Junction to Ambient	50	$^{\circ}C/W$
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case	0.45	$^{\circ}C/W$

Note ① : Max. current is limited by bonding wire.

Note ② : UIS tested and pulse width are limited by maximum junction temperature $150^{\circ}C$.

Note ③ : Surface Mounted on $1in^2$ FR-4 board with 1oz.



N-Channel Enhancement Mode MOSFET

Electrical Characteristics ($T_J=25^{\circ}\text{C}$, Unless Otherwise Noted)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Static Electrical Characteristics						
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS}=0V, I_D=250\mu A$	200	---	---	V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS}=200V, V_{GS}=0V$	---	---	1	μA
		$V_{DS}=160V, V_{GS}=0V, T_J=125^{\circ}\text{C}$	---	---	100	μA
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu A$	2.5	---	4.5	V
I_{GSS}	Gate Leakage Current	$V_{GS}=\pm 20V, V_{DS}=0V$	---	---	± 100	nA
$R_{DS(on)}$	Drain-Source On-state Resistance	$V_{GS}=10V, I_D=35A$	---	9.5	11	m Ω
Dynamic Characteristics^⑤						
C_{iss}	Input Capacitance	$V_{GS}=0V, V_{DS}=100V, \text{Freq.}=1.0\text{MHz}$	---	10656	---	pF
C_{oss}	Output Capacitance		---	389	---	
C_{riss}	Reverse Transfer Capacitance		---	16	---	
$T_{d(on)}$	Turn-on Delay Time	$V_{GS}=10V, V_{DD}=100V, I_D=55A, R_G=4.7\Omega$	---	46	---	nS
T_r	Turn-on Rise Time		---	21	---	
$T_{d(off)}$	Turn-off Delay Time		---	88	---	
T_f	Turn-off Fall Time		---	18	---	
Q_g	Total Gate Charge	$V_{GS}=10V, V_{DD}=100V, I_D=55A$	---	145	---	nC
Q_{gs}	Gate-Source Charge		---	49	---	
Q_{gd}	Gate-Drain Charge		---	27	---	
Source-Drain Characteristics						
I_S	Continuous Source Current		--	---	110	A
V_{SD}	Diode Forward Voltage	$I_S=70A, V_{GS}=0V$	---	---	1.2	V
t_{rr}	Reverse recovery time	$I_F=55A, diF/dt=100A/\mu s$	---	185	---	ns
Q_{rr}	Reverse recovery charge		---	469	---	nC

Note ④: Pulse test (pulse width $\leq 300\mu s$, duty cycles $\leq 2\%$).

Note ⑤: Guaranteed by design, not subject to production testing.


N-Channel Enhancement Mode MOSFET
Typical Characteristics


Figure 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

N-Channel Enhancement Mode MOSFET




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics





Figure 9: Maximum Forward Biased Safe Operating Area

N-Channel Enhancement Mode MOSFET
TO-247 Package Outline Dimensions


Symbol	Dimensions In Millimeters	
	Min.	Max.
A	4.90	5.20
A1	2.31	2.51
A2	1.9	2.1
b	1.16	1.26
b2	1.96	2.06
b4	2.96	3.06
b6	-	2.25
b7	-	3.25
C	0.59	0.66
D	20.90	21.20
D1	16.25	16.85
D2	1.05	1.35
E	15.75	16.10
E1	13.00	13.60
e	5.436 BSC	
L	19.80	20.20
L1	-	4.30
P	3.40	3.60
P1	7.00	7.40
S	6.05	6.25
T	9.80	10.20