

## P-Channel Enhancement Mode MOSFET


### Features

- Low  $R_{ds(on)}$  for low conduction loss
- Reliable and Rugged
- ROHS Compliant & Halogen-Free

### Applications

- Power Management in Desktop Computer
- DC/DC Converters

### Pin Description



$V_{bss}$	-60	V
$R_{ds(ON)-Typ}$	33	m $\Omega$
$I_D$	-25	A

### Absolute Maximum Ratings ( $T_C=25^\circ\text{C}$ , Unless Otherwise Noted)

Symbol	Parameter	P-Channel	Unit
$V_{bss}$	Drain-Source Voltage	-60	V
$V_{GSS}$	Gate-Source Voltage	$\pm 20$	V
$T_J$	Maximum Junction Temperature	-55 to 150	$^\circ\text{C}$
$T_{STG}$	Storage Temperature Range	-55 to 150	$^\circ\text{C}$
$I_{DM}^{①}$	Pulse Drain Current Tested	-60	A
$I_D$	Continuous Drain Current	-25	A
$P_D$	Maximum Power Dissipation	90	W
$E_{AS}$	Single Pulse Avalanche Energy	300	mJ

### Thermal Characteristics

Symbol	Parameter	Rating	Unit
$R_{\theta JC}$	Thermal Resistance Junction-Case	1.4	$^\circ\text{C}/\text{W}$

Note ① : Max. current is limited by bonding wire.

Note ② : UIS tested and pulse width are limited by maximum junction temperature  $150^\circ\text{C}$ .

Note ③ : Surface Mounted on  $1\text{in}^2$  FR-4 board with 1oz.









**P-Channel Enhancement Mode MOSFET**






**Electrical Characteristics** ( $T_J=25^{\circ}\text{C}$ , Unless Otherwise Noted)


Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
<b>Static Electrical Characteristics</b>						
$BV_{DSS}$	Drain-Source Breakdown Voltage	$V_{GS}=0V, I_D=-250\mu A$	-60	---	---	V
$I_{DSS}$	Zero Gate Voltage Drain Current	$V_{DS}=-48V, V_{GS}=0V$	---	---	-1	$\mu A$
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=-250\mu A$	-1.0	---	-2.5	V
$I_{GSS}$	Gate Leakage Current	$V_{GS}=\pm 20V, V_{DS}=0V$	---	---	$\pm 100$	nA
$R_{DS(on)}$	Drain-Source On-state Resistance	$V_{GS}=-10V, I_D=-20A$	---	33	40	m $\Omega$
gfs	Forward Transconductance	$V_{DS}=-10V, I_D=-10A$	25	---	---	S
<b>Dynamic Characteristics<sup>⑤</sup></b>						
$C_{iss}$	Input Capacitance	$V_{GS}=0V, V_{DS}=-30V, \text{Freq.}=1\text{MHz}$	---	3130	---	pF
$C_{oss}$	Output Capacitance		---	321	---	
$C_{rss}$	Reverse Transfer Capacitance		---	212	---	
$T_{d(on)}$	Turn-on Delay Time	$V_{DD}=-30V, V_{GS}=-10V, R_G=3\Omega, R_L=1.5\Omega$	---	12	---	nS
$T_r$	Turn-on Rise Time		---	15	---	
$T_{d(off)}$	Turn-off Delay Time		---	38	---	
$T_f$	Turn-off Fall Time		---	15	---	
$Q_g$	Total Gate Charge	$V_{DS}=-30V, V_{GS}=-10V, I_D=-10A$	---	46	---	nC
$Q_{gs}$	Gate-Source Charge		---	9.5	---	
$Q_{gd}$	Gate-Drain Charge		---	10.5	---	
<b>Source-Drain Characteristics</b>						
$V_{SD}^{④}$	Diode Forward Voltage	$V_{GS}=0V, I_S=-10A, T_J=25^{\circ}\text{C}$	---	---	-1.1	V
$t_{rr}$	Reverse Recovery Time	$I_F=-10A, di/dt=100A/\mu s, T_J=25^{\circ}\text{C}$	---	47	---	nS
$Q_{rr}$	Reverse Recovery Charge		---	53	---	nC

Note ④: Pulse test (pulse width 300us, duty cycle 2%).

Note ⑤: Guaranteed by design, not subject to production testing.

**P-Channel Enhancement Mode MOSFET**
**Typical Characteristics**

**Figure 1 Output Characteristics**

**Figure 2 Transfer Characteristics**

**Figure 3 Rdson- Drain Current**

**Figure 4 Rdson-Junction Temperature**

**Figure 5 Gate Charge**

**Figure 6 Source- Drain Diode Forward**

**P-Channel Enhancement Mode MOSFET**

**Figure 7 Capacitance vs Vds**

**Figure 8 Safe Operation Area**

**Figure 9  $BV_{DSS}$  vs Junction Temperature**

**Figure 10  $I_D$  Current De-rating**

**Figure 11 Normalized Maximum Transient Thermal Impedance**

**P-Channel Enhancement Mode MOSFET**
**TO-252 Package Outline Dimensions**


Symbol	Dimensions in Millimeters		Dimensions in Inches	
	Min	Max	Min	Max
A	2.25	2.65	0.089	0.104
A1	0.00	0.15	0.000	0.006
A2	2.20	2.40	0.087	0.094
b	0.50	0.70	0.020	0.028
b1	0.70	0.90	0.028	0.035
c	0.46	0.66	0.018	0.026
c1	0.46	0.66	0.018	0.026
D	6.30	6.70	0.248	0.264
D1	5.20	5.40	0.205	0.213
E	5.30	5.70	0.209	0.224
E1	1.40	1.60	0.055	0.063
H	9.40	9.90	0.370	0.390
e	2.30 TYP		0.09 TYP	
L	1.40	1.77	0.055	0.070
L1	0.50	0.70	0.020	0.028
θ	0°	8°	0°	8°